

Ozone generator

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.ozonetech.com

ACT-5000

ACT-5000 is built with a stainless steel chassis with all controls easily accessible on the unit's back side. The ozone generator has built-in monitoring of all vital parameters and shuts down the unit in case of any errors. The unit can also be controlled via the built-in 4-20 mA interface.



Technical specification

Ozone production	
Concentration, max	11 ppm
Production	0 – 3.5 g/h
Feed gas (air)	
Quality	Indoor air [21% O ₂]
Filter class	F-7
Fan capacity, max	130 m ³ /h
Ambient conditions	
Temperature	0 to +40 °C (+32 to +104 °F)
Humidity, max	85 % (R. H.) non-condensing
Electrical connections	
Voltage rating	230 VAC, 50 Hz
- Optional	115 VAC, 60 Hz
Power consumption, max	125 W
Dimensions	
Size (H x B x D)	270 x 130 x 130 mm (10.6 x 5.1 x 5.1 in)
Weight	3.5 kg (7.7 lbs)
IP class	20



© Ozonetech

ozonetech.
a MELLIFIQ brand

Ozone generator

Advantages

- Stainless steel chassis
- Very low noise level
- Adjustable ozone production (0-100%)
- Compact design
- Easy to maintain
- Built-in digital input and output
- Built-in 4-20 mA interface

Elektravägen 53
SE-126 30 Hägersten, Sweden
+46 10 252 30 00
www.ozonotech.com



© Ozonotech

ozonotech.
a MELLIFIQ brand